



## DGB 24 TF BC

Portable BC Max Range


 POWER (PRP):  
**22 kVA / 17 kW**
 FREQUENCY  
**50Hz**
 VOLTAGE  
**400/230V**
 WEIGHT WITH WHEELS:  
**220kg**
 DIMENSIONS WITH WHEELS:  
**L: 1056 mm  
W: 800 mm  
H: 819 mm**

Image for orientation purposes. Transport kit is included in the standard scope of delivery. Dagartech reserves the right to modify the data in this technical sheet without prior notice.

 Unleaded gasoline

 EU Stage V

 Air-cooled

 Moving chassis

 CE certified

## 1. General technical data

### General technical data

Engine	<b>VANGUARD 6134</b>	
Alternator	<b>LINZ E1S13M E/2</b>	
Frequency	50Hz	
Voltage	400/230V	
Work regime (rpm)	3000	
Type of regulation	Electronic	
Power factor ( $\cos \varphi$ )	0,8	
Tank (l)	25	
Type of start-up	Electric	
<b>PRP (kVA / kW)</b>	<b>22 / 17</b>	

The transport kit is included in the standard scope of supply of this equipment.

### Powers<sup>1</sup> (p.f. $\cos \varphi$ 0,8)

 PRP (kVA / kW) **22 / 17**

<sup>1</sup>PRP: Prime Power according to ISO8528-1.

### Directives and Regulations

#### ENVIRONMENTAL CONDITIONS STANDARD ISO 8528-1:2018: 25°C, 100kPa and 30% relative humidity:

- **Prime Power (PRP):** Data on electrical power available at variable load without limit of hours per year. An overload of 10% is allowed for 1h out of 12. According to ISO 8528-1:2018.
- **Emergency Standby Power (ESP):** Data on electrical capacity available at variable load in case of emergency according to ISO 8528-1:2018.

#### The DAGARTECH Generator bears the CE marking which includes the following directives:

- **2006/42/EC.** Machine Safety Directive.
- **EN ISO 8528-13:2016.** Part 13: Safety. Alternating current generators powered by reciprocating internal combustion engines.
- **2014/30/EU.** Electromagnetic Compatibility Directive.
- **2000/14/EC.** Noise Emissions Directive. Sound power levels evaluated in accordance with the procedure laid down in the directive.
- **Directive 2011/65/EU** on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS<sup>2</sup>).

400/230V · 50Hz (3000 rpm)

VANGUARD 6134 | LINZ E1S13M E/2

**2.1.**  
**General technical data of the engine**

<b>Make and model</b>	<b>VANGUARD 6134</b>
r.p.m.	3000
Continuous power - 3,000 rpm (kW/m)	N/A
Max. net power - 3600 rpm (kW/m)	26,1*
Type of regulation	Electronic
Fuel	Unleaded gasoline
No. of cylinders	2
Cylinder capacity (c.c.)	993
Compression ratio	8,2:1
Maximum torque (Nm)	N/A
Cooling system	Air-cooled
Start-up Method	Electric



4-STROKE-PETROL ENGINE. AIR-COOLED.



\* Gross power data for VANGUARD and BRIGGS-STRATTON engines.

**2.2. Fuel**

<b>Type of fuel</b>	Unleaded gasoline
Tank capacity	25

**2.3. Consumption and autonomy**

	Consumption (l/h)		Autonomy (h)	
	PRP	ESP	PRP	ESP
75%	4,2	-	6	-
100%	N/A	-	N/A	-

**2.4. Lubrication system**

Oil capacity (l)	2,3
Oil consumption (L/H)	N/A

**3. Alternator specifications**
**3.1. General technical data of the alternator**

<b>Make and model</b>	<b>LINZ E1S13M E/2</b>
No. of poles	2
Insulation class	H
Mechanical protection index	IP23
Voltage regulator	Compound
Power PRP 40°C (kVA)	27
No. of phases	3
Power factor ( $\cos \varphi$ )	0,8


**Standard regulations that the alternator meets:**

Directives: 2006/42, 2006/95, 2004/108 and amendments thereto.

Complies with: EN 60034-1, CEI 2-3, IEC34-1, VDE 0530, BS 4999-5000, N.F. 5111.


**2-pole alternator, Compound.**

No maintenance required.

**Winding protection** by impregnation with tropicalised epoxy resin.

400/230V · 50Hz (3000 rpm)

VANGUARD 6134 | LINZ E1S13M E/2

## 5. Standard scope of supply for the BC Max range and available options

### STANDARD SCOPE OF DELIVERY

- VANGUARD 6134 Electric starter engine
- Alternator LINZ E1S13M E/2 · Compound
- Fuel tank of 25 litres capacity
- Compact electro-welded steel frame with anti-vibration dampers
- Top protective metal plate
- IP55 electrical panel with IP67 power sockets and built-in protective door on the chassis

*The electrical panel complies with the ICT-BT-33 construction standard*

*The additional metal protective door provides robustness and reliability for the most adverse working conditions. It includes:*

- Inner protective window (for electrical devices).
- Emergency stop button.
- Individual and differential circuit breaker protection.
- Hour meter.
- Voltmeter.

Transport kit (includes solid puncture-proof wheels, handles, and stand).

Supply without engine lubrication oil

Engine oil protection\*

Fuel stopcock

Alternator thermal protection

### AVAILABLE OPTIONS

**Kit 2.** Alternator with AVR

*Option available in models with Honda engine.*

*Check the availability of this option based on the model.*

### POWER SOCKETS CONFIGURATION

	IP67	CEE IP67	CEE IP67
	Schuko	2P + T 32A	3P + N + T 32A
<b>DGH 12000 BC</b>	2	1	-
<b>DGH 12 TF BC</b>	2	-	1
<b>DGH 15 TF BC</b>	2	-	1
<b>DGH 24 TF BC</b>	2	-	1

\* Not available on models fitted with a VANGUARD engine.

**Caption**

Included

Optional

Not available

Consult



---

[info@dagartech.com](mailto:info@dagartech.com)

T +34 976 141 655

---



**CUSTOM  
ENERGY  
SOLUTIONS**

[dagartech.com](http://dagartech.com)