

Emergency Balance Range

⚡ POWER (PRP / ESP):
56 / 61 kVA (45 / 49 kW)

EU0 EMISSIONS LEVEL:
EU Stage 0

📡 FREQUENCY
60Hz

⚡ VOLTAGE
208/120V

CE CE CERTIFIED

BGPW 50 ST

BGPSW 50 ST

1. General technical data

1.1. Version, dimensions and weight

Version	Open	Soundproofed
Dimensions	2K1B	BK1B
L (mm)	1795	2288
W (mm)	950	972
H (mm)	1252*	1301
Weight with liquids and without fuel (kg)	850	1300

1.2. Main technical data

Engine	PERKINS 1103A-33TG1	
Alternator	STAMFORD S1L2-Y	
Fuel	Diesel	
Type of execution	G2	
Control panel	DSE 6120 MKIII	
Fuel tank (l)	110	110
Sound level-Lp(A) (dB(A)@1m) ¹	N/A (Indoor)	75
Sound level-Lp(A) (dB(A)@7m) ¹	N/A (Indoor)	67
Sound power-LW(A) (dB(A))	N/A (Indoor)	90

¹The sound levels may vary depending on the measurement conditions.

Voltage	PRP ² (KVA/KW)	ESP ² (KVA/KW)	PRP Amperage (A)	ESP Amperage (A)
208/120V	56 / 45	61 / 49	155,4	169,3
220/127V	56 / 45	61 / 49	147	160,1
380/220V	55 / 44	60 / 48	83,6	91,2
480/277V	56 / 45	61 / 49	67,4	73,4

²PRP: Continuous power ("Prime Power"). ESP: Emergency Standby Power according to ISO8528-1.

Tolerance of maximum active power (kW) ±5%

Directives and Regulations

ENVIRONMENTAL CONDITIONS STANDARD ISO 8528-1:2018: 25°C, 100kPa and 30% relative humidity:

- **Prime Power (PRP):** Data on electrical power available at variable load without limit of hours per year. An overload of 10% is allowed for 1h out of 12. According to ISO 8528-1:2018.
- **Emergency Standby Power (ESP):** Data on electrical capacity available at variable load in case of emergency according to ISO 8528-1:2018.

The DAGARTECH Generator bears the CE marking which includes the following directives:

- **2006/42/EC.** Machine Safety Directive.
- **EN ISO 8528-13:2016.** Part 13: Safety. Alternating current generators powered by reciprocating internal combustion engines.
- **2014/30/EU.** Electromagnetic Compatibility Directive.
- **2000/14/EC.** Noise Emissions Directive. Sound power levels evaluated in accordance with the procedure laid down in the directive.
- **Directive 2011/65/EU** on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS 2).

* Confirm the height of the equipment. This value may vary depending on whether a lifting pole is included in the standard scope of supply.

2. Engine specifications

208/120V · 60Hz (1800 rpm)			BGPW 50 ST		BGPSW 50 ST	
2.1. General technical data of the engine	Version		Open		Soundproofed	
	Make and model		PERKINS 1103A-33TG1			
	Emissions		EU Stage 0			
	r.p.m.		1800			
	Maximum ESP power (kWm)		53,9			
	Power PRP (kWm)		48,8			
	Fuel		Diesel			
	No. of cylinders		3			
	Cylinder capacity (c.c.)		3300			
	Compression ratio		17,25:1			
	Cooling system		Water-cooled			
	Type of regulation		Mechanical			
	Type of engine/injection/suction		Diesel / direct / Turbocharged			
2.2. Fuel	Type of fuel		Diesel			
	Fuel tank capacity		110		110	
2.3. Consumption and autonomy			Open		Soundproofed	
	Consumption (l/h)		Autonomy (h)		Autonomy (h)	
	PRP	ESP	PRP	ESP	PRP	ESP
	50%	7,1	-	15,5	-	15,5
	75%	9,9	-	11,1	-	11,1
	100%	12,9	14,3	8,5	7,7	8,5
	7,7					
2.4. Cooling system	Version		Open		Soundproofed	
	Fan flow (m³/min)		70		70	
	Radiator back pressure (kPa)		5		5	
	Fan power consumption (kW)		1,7			
	Total refrigerant capacity (l)		10,2			
2.5. Lubrication system	Oil capacity (l)		8,3			
	Oil consumption (N/A0)		0N/A			
2.6. Intake system	Combustion air intake flow (m³/min)		3,9			

<<Tension>> · <<Frecuencia>> (<<rpm>> rpm)		<<Modelo>>	<<Modelo insonorizado>>
2.7. Starter system	Version	Open	Soundproofed
	No. of batteries	1	
	Battery characteristics	12V 60Ah	
	Start-up voltage (V)	12V	
	Common data for both versions		
2.8. Exhaust system	Exhaust gas flow (m³/min)	8,8 [PRP]	9,5 [ESP]
	Exhaust gas temperature (°C)	510 [PRP]	551 [ESP]
	Version	Open	Soundproofed
	Exhaust outside diameter (mm)	2,5" (Ø 65,5)	2" (Ø 50,8)
	Exhaust attenuation level (dB(A))	-10	-25
	Max. exhaust back pressure (kPa)	15	

Radiator level sensor not available for Baudouin 4M06 series engines.

3. Alternator specifications

3.1. General technical data of the alternator

Voltage		208/120V	220/127V	380/220V	480/277V
Model		STAMFORD S1L2-Y	STAMFORD S1L2-Y	STAMFORD UCI224E	STAMFORD S1L2-Y
No. of poles		4	4	4	4
Insulation class		H	H	H	H
No. of threads		12	12	12	12
Mechanical protection index		IP23	IP23	IP23	IP23
Voltage Regulator (AVR)		AS540	AS540	AS440	AS540
Voltage regulation		±1%	±1%	±1%	±1%
ESP power 27°C (kVA)		72,6	76,2	63	82,5
Power PRP 40°C (kVA)		66	69,3	60	75
No. of phases		3	3	3	3
Power factor (cos φ)		0,8	0,8	0,8	0,8
		Performance η (%)			
Voltage		50%	75%	100%	110%
<<Tension>>		93,4%	92,7%	91,1%	90,2%
220/127V		93,2%	92,6%	91,1%	90,2%
380/220V		N/A	N/A	88,8%	88,5%
480/277V		93,2%	92,6%	91,0%	90,0%

i Standard regulations that the alternator meets:

AS 1359 | IEC 34-11 | BS EN 60034-1 | VDE 0530 | BS 5000 | CAN/CSA-C22.2-100 | NEMA MG1-32

Low wave distortion: THD (100% load) = 2% | THF < 2%

Complies with: EN61000-6-3, EN61000-6-2 regarding radio interference.

208/120V · <<Frecuencia>> (<<rpm>> rpm)

<<Motor>> | <<Alternador>>

4. Bench Specifications

- Unit mounted on **electro-welded high-resistance steel bench**, painted with electrostatic epoxy-polyester powder paint.
- Connection of the assembly to the bench by means of **anti-vibration dampers**.
- **Fuel tank located on the bench itself**. The engine is equipped with a measuring gauge and fuel system.
- **Tested in a salt spray chamber according to ASTM B-117-09, resistance 500h**.

5. Soundproof Canopy Specifications



i The canopy is part of the scope of supply of the soundproof generator sets.
 Open generators do not include a canopy.

- **Electro-welded canopy made of high resistance galvanized steel** painted with electrostatic epoxy-polyester powder paint
- Interior soundproofing by means of **a lining with soundproofing material**.
- **Attenuation silencer -25dB(A)** for the evacuation of gases to the outside with protective cover.
- **Tested in a salt spray chamber according to ASTM B-117-09, resistance 720H. IP44 mechanical protection degree**.

THE CANOPIES OF THE EMERGENCY BALANCE RANGE ARE MADE OF HIGH-RESISTANCE GALVANIZED STEEL AND ARE ELECTRO-WELDED AND PAINTED WITH ELECTROSTATIC EPOXY-POLYESTER POWDER PAINT.



In addition, they are equipped with a coating with noise-insulating material (polyurethane foam with outer veil). We also incorporated a silencer **attenuation device for the evacuation of gases to the outside**, featuring a rain cap.

*Our canopies are tested in a salt spray chamber according to standard **ASTM B-117-09** (resistance 720H. IP44 mechanical **protection grade**).*

6. Control panel

6.1. Main elements of the control panel

- Protection panel, distribution with **automatic control module** which allows you to work in manual, automatic or signal mode.
- Push button** for **emergency stop**.
- Deep Sea Electronics battery charger**, designed to be permanently connected to the battery and maintain 100% of the charge. The charger switches to float mode when charging is complete:

Model	DSE 9150 12V, 3A
-------	------------------

Protections:

- 4-pole magnetothermic protection** against overloads and short circuits.
- Protection fuses** for the control set.

6.2. Circuit breaker

Modelo 208/120V	Chint 250A 4P
Modelo 220/127V	Chint 160A 4P
Modelo 380/220V	Chint 100A 4P
Modelo 480/277V	Chint 80A 4P

6.3. Control module



- | | |
|--|--|
| 1. Transfer to the generator (manual mode) | 6. Manual mode |
| 2. Start engine (manual mode) | 7. Genset stop |
| 3. Silence alarm | 8. MAIN NETWORK transfer (manual mode) |
| 4. Automatic mode | 9. Navigation keyboard |
| 5. Test mode | 10. Main status and instrument display |

Model	DSE 6120 MKIII
-------	----------------

The DSE 6120 MKIII is an Automatic Mains Failure (AMF) control module designed for use in a wide range of applications with diesel or gas generators. Upon detecting a power supply interruption, it automatically starts the generator and shuts it down once the mains power is restored. It also allows operation in manual and test modes.

This module allows monitoring of multiple engine parameters and displays alerts, statuses, and alarms on a backlit LCD screen. It is compatible with both electronic (CAN) and non-electronic engines, offering configurable inputs and outputs to suit various needs. Additionally, it includes USB communication and allows expansion via DSENet®.

Its configuration is straightforward and can be done using the DSE Configuration Suite software or directly from its front panel. It also features advanced functionalities such as event and performance monitoring, remote communications, and PLC programming capabilities.

The module dimensions are 216 mm x 158 mm x 43 mm, with a panel cutout of 184 mm x 137 mm and a maximum panel thickness of 8 mm. It is an ideal solution for applications that require reliable control and monitoring of the generator.

Environmental Tests that the module passes:

| BS EN 61000-6-2 (electromagnetic compatibility) | BS EN 61000-6-4 (electromagnetic compatibility) | BS EN 60950 (electrical safety) | BS EN 61000-6-2 (Temperature) | BS EN 60068-2-6 (Vibration) | BS EN 60068-2-30 (Humidity) | BS EN 60068-2-27 (Shock).

208/120V · 60Hz (1800 rpm)

PERKINS 1103A-33TG1 | STAMFORD S1L2-Y

6.3. Control module


Standard ✓

DSE 6120 MKIII


Option □

DSE 7320 MKII

Model

Operating modes

STOP mode



MANUAL mode



TEST mode



AUTO mode



Module configuration options

PC



Generator readings

Generator voltage (F-F)



Generator voltage (F-N)



Generator current (A)



Generator frequency



Generator load F-N (kW / kVA / kVA)



Total generator load (kW / kVA / kVA)



Average generator power factor


 Accumulated generator load
(kW, kVAh, kWh, kVAh)


Network readings

Network voltages (ph-N)



Network voltages (ph-ph)



Grid frequency



Network current (A)



Network load ph-N (kW / kVA / kVA)



Total network load (kW / kVA / kVA)



Engine readings

Coolant temperature



Oil pressure



Engine fuel level



Engine battery volts



Engine speed



Engine run time



Caption

Included

Optional

Not available

Consult

Readings available at control module level.

Confirm the availability of these readings for this generator and engine.

Ask us for further readings in generating sets equipped with electronically managed engines and DSE 7320MKII control module.


**DO YOU WANT A SUPERIOR
PERFORMANCE CONTROL MODULE?**

 Contact us
and tell us what you need.

208/120V · 60Hz (1800 rpm)

PERKINS 1103A-33TG1 | STAMFORD S1L2-Y

6.3. Control module


Standard ✓

DSE 6120 MKIII


Option □

DSE 7320 MKII

Model

Engine protections

High water temperature	✓	✓
Low oil pressure	✓	✓
Low water level	✓	✓
Fuel reserve by sensor	✓	✓
Second fuel tank control	✓	✓
Shutdown failure	✓	✓
Battery voltage failure	✓	✓
Battery charge alternator failure	✓	✓
Overspeed	✓	✓
Underfrequency	✓	✓
Failure to start	✓	✓
Emergency stop	✓	✓
Maintenance notice	✓	✓
Maintenance Alert	✓	✓
Low load operation warning	□	□

Alternator protections

High frequency	✓	✓
Low frequency	✓	✓
High voltage	✓	✓
Low voltage	✓	✓
Short circuit	✓	✓
Asymmetry between phases	□	□
Incorrect phase sequence	✗	✓
Reverse power	✗	✓
Breaker Trip 4 poles	□	□
Overpressure alarm	✓	✓

Counters

Hour meter	✓	✓
Kilowatt meter	✓	✓
Starter counter	✓	✓

Caption

- ✓ Included
- Optional
- ✗ Not available
- ℹ Consult

Readings available at control module level.

Confirm the availability of these readings for this generator and engine.

Ask us for further readings in generating sets equipped with electronically managed engines and DSE 7320MKII control module.



DO YOU WANT A SUPERIOR PERFORMANCE CONTROL MODULE?

Contact us and tell us what you need.

6.3. Control module


Standard ✓

Option □

Model	DSE 6120 MKIII	DSE 7320 MKII
Communications		
RS232	✗	✓
RS485	✗	✓
USB communication port	✓	✓
Modbus IP	□ DSE 855/890/891	□ DSE 855/890/891
Modbus RS 485	□ DSE 855/890/891	✓
PC Software (Mimic)	✓	✓
GSM/GRPS MODEM	□ DSE 890	□ DSE 890
Remote display < 1km	✗	□ DSE 2520
Remote monitoring	□ DSE 855/890	□ DSE 855/890
Input expansion	□ DSE 2130 8 inputs	□ DSE 2130 8 inputs
Input expansion (Thermocouple)	□ DSE 2133	□ DSE 2133
Output expansion	□ DSE 2152/2157 8 inputs	□ DSE 2152/2157 8 inputs
Status LED expansion	□ DSE 2548	□ DSE 2548
SNMP protocol	□ DSE 892	□ DSE 892
Services		
Configurable alarm history	250	250
External start	✓	✓
Start-up inhibition	□	□
Network Failure Start	✓	✓
Activation of group counter	✓	✓
Activation of grid and group counter	✓	✓
Control of fuel transfer	✓	✓
Motor temperature control	✓	✓
Forced group operation	✓	✓
Free programmable alarms	✓	✓
Group start function in test mode	✓	✓
Free programmable outputs	✓	✓
Multilingual	✓	✓
Special applications		
GPS localisation	□ DSE 890	□ DSE 890
Calendar scheduler	✓	✓
DSE configuration suite via PC	✓	✓
Front panel module configuration with PIN	✓	✓
Alternative work	✗	✓
Programmable PLC	✓	✓
Power save mode	✓	✓
Alternative configurations	✓	✓
Dummy load control / load shedding	✗	✓ 5 Stage dummy load

Caption

- ✓ Included □ Optional
 ✗ Not available ⓘ Consult

Readings available at control module level.

Confirm the availability of these readings for this generator and engine.

Ask us for further readings in generating sets equipped with electronically managed engines and DSE 7320MKII control module.



DO YOU WANT A SUPERIOR PERFORMANCE CONTROL MODULE?

Contact us and tell us what you need.

208/120V · 60Hz (1800 rpm)

PERKINS 1103A-33TG1 | STAMFORD S1L2-Y

7. Detailed supply scope

Engine

ENGINE PERKINS 1103A-33TG1, EU STAGE 0 OF 1800 RPM, WATER-COOLED AND WITH MECHANICAL.

- Engine Diesel of 3 cylinders in line and 4-stroke, with regulation Mechanical by means of a fuel pump, original from the manufacturer.
- Injection system direct and suction Turbocharged. With particle separator filter, original from the manufacturer.
- Industrial exhaust gas silencer of -10 dB(A).  INCLUDED
- Residential exhaust silencer of <<Nivel de atenuacion esc INCLUDED >izado (dB(A))>>dB(A).
- Refrigeration through cooling liquid, fully distributed in the closed circuit run by an engine driven pump.
- Crankshaft-driven pump lubrication system. The filter is a full-flow insert cartridge, front housing, original from the engine manufacturer.
- Air intake system for turbo-fed combustion with two-stage filter, original from the manufacturer.
- Electric motor starting system, battery (no maintenance) with disconnecter and load alternator driven by the starter motor 12V.
- Protection from hot and moving parts.

Alternator

ALTERNATOR STAMFORD S1L2-Y OF 12 WIRES AND 4 POLES, BRUSHLESS AND WITH ELECTRONIC VOLTAGE REGULATION TYPE AVR (AS540)

- Alternator of 4 poles, brushless. Robust mechanical structure with easy access to connections and components. Insulation class H, coil pitch 2/3 and self-excited AVR.
- With protection degree IP23 and insulation class H.
- Protection with premium epoxy resins. High voltage parts are impregnated under vacuum, which always means very good insulation.

Do you have any queries about the supply?
 Contact us.



Caption:



INCLUDED IN OPEN GENERATOR SETS



INCLUDED IN SILENT GENERATOR SETS

208/120V · 60Hz (1800 rpm)

PERKINS 1103A-33TG1 | STAMFORD S1L2-Y

Bench

- Bench made of high-strength electro-welded steel.
- Painted with electrostatic epoxy-polyester powder paint.
- Anti-vibration dampers from the engine block to the bedplate.
- Fuel tank included on the bench itself. Equipped with cleaning record to facilitate maintenance work from 90 kVA of power onward.
- With measuring gauge and installation of fuel to the engine.
- Liquid drainage connection to the outside.
- **Bench tested in a salt spray chamber according to ASTM B-117-09 (500h resistance).**

Soundproofed canopy (not included in open models)

- Electro-welded canopy of high resistance galvanized steel.
- Painted with electrostatic epoxy-polyester powder paint.
- Interior soundproofing by means of coating with noise-insulating material (polyurethane foam with outer veil).
- With IP44 mechanical protection level.
- **Canopy tested in salt spray chamber according to ASTM B-117-09 (resistance 720h).**

Control panel

- **DeepSea Electronics automatic control module, DSE 6120 MKIII which allows you to work in manual, automatic or signal mode.**
 - It offers multiple event logging and is fully configurable through DeepSea Electronics' free-access specific configuration software.
 - Three-phase network and group detection with measurement for configurations upon network failure.
- **DeepSea Electronics battery charger DSE 9150 12V, 3A.**
 - Designed to be permanently connected to the battery and maintain 100% of the charge. The charger switches to float mode when charging is complete.
- **Protections:**
 - 4-pole magnetothermic protection against overloads and short circuits.
 - Protection fuses for the control set.

208/120V · 60Hz (1800 rpm)

PERKINS 1103A-33TG1 | STAMFORD S1L2-Y

7. Detailed supply scope

Other equipment

- Interior fuel filling nozzle.
- Tropicalised Radiator for work at 50 °C*
- Prepared for maintenance intervals every 500 hours*.
- Push button for emergency stop.
- Reinforced pole centrally-mounted from 90 kVA (Optional for models below 90kVA).

8. Featured options available



Kit 1: Network failure

Adding an **engine heater** to your generator will ensure that your genset starts smoothly in the event of any failure in the electrical network, and without cold or moisture becoming an issue.



The readings and alarm kit is included within the standard supply scope of the equipment starting from 275kVA of power.

Kit 2: Readings and alarm¹

Your generator can provide you with very useful information in the event of any malfunction, maintenance work, or simply during its operation. If this is an important aspect for you, do not hesitate to include this kit in its equipment, which includes:

- Radiator level alarm sensor.
- Oil pressure reading sensor.
- Temperature reading sensor.

¹ Radiator level sensor not available for Baudouin 4M06 series engines.




Kit 3: Exhaust installation

If you need a **versatile solution for venting gases from your installation to the outside**, choose this kit, equipped with 2 clamps and 3 meters of galvanized steel flexible hose.



✓ AVAILABLE IN OPEN GENERATOR SETS



Check the availability of these options according to the model and, if you don't find what you're looking for, contact us. We have many more options to offer you.

* Consult the specification according to the model.

¹ Maintenance intervals may vary depending on the climate and working conditions.

9. Even more options



24 hour tank


 External ROTH tanks
DUO SYSTEM

AUTONOMY OPTIONS

Increase the autonomy of your generator up to 48 hours, including special tanks

You can choose between different integrated tanks to increase the autonomy of the unit up to 48 hours of operation. You can also incorporate automatic fuel transfer systems for supply from external tanks.

— External tanks:

- External tank 400 l (ROTH DUO SYSTEM).
- External tank 620 l (ROTH DUO SYSTEM).
- External tank 1,000 l (ROTH DUO SYSTEM).
- External tank 1,500 l (ROTH DUO SYSTEM).


 Fuel particle separator
filter

ENGINE - ALTERNATOR OPTIONS

You can choose between different integrated tanks to increase the autonomy of the unit up to 48 hours of operation. You can also incorporate automatic fuel transfer systems for supply from external tanks.

- Electronic engine regulation/management (for models with mechanical regulation).
- Fuel particle separator filter.
- Manual oil drainage pump.
- 6-way fuel valve kit.
- Alternator anti-condensation heaters.
- Superior alternator impregnation systems.
- AVR MX341 + PMG $\pm 1\%$ STAMFORD.
- AVR MX321 + PMG $\pm 0.5\%$ STAMFORD.
- Alternator change supplement (for units with MECC ALTE alternator).

208/120V · 60Hz (1800 rpm)

PERKINS 1103A-33TG1 | STAMFORD S1L2-Y



Central lifting pole

MECHANICAL OPTIONS

- Retention tray (see change of dimensions).
- Liquid leak sensor (requires retention tray).
- SilentBlocks for levelling.
- Damping - anti-vibration springs.
- Lifting pole (for generators < 85kVA).
- Non-standard RAL color  AVAILABLE



DSE 2157



DSE 334 network surveillance

COMMUNICATION OPTIONS

- DSE 7320 MKII control card extra price (for models with the DSE 6020 MKII control card in the standard scope of supply).
- DSE 2157 8 potential free output (requires DSE 7320MKII).
- DSE 2130 8 inputs (requires DSE 7320MKII).
- DSE 2548 8 LED diodes (requires DSE 7320MKII).
- DSE 855.
- DSE 890 webnet.
- DSE 7420 module.
- DSE 334 network surveillance.



Socomec motorised switchboard

POWER OPTIONS

- Differential protection.
- As an option, you can include a switch cabinet attached to the generating set.
- Switching with Schneider contactors. 25 to 125 A.
- Socomec motorised switches: $\geq 125A$.

Caption:




✓ AVAILABLE IN OPEN GENERATOR SETS



✓ AVAILABLE IN SILENT GENERATOR SETS

Installation drawing BGPW 50 ST - standard open model






T +34 976 141 655
info@dagartech.com
dagartech.com



- 14 -

T +34 976 141 655
info@dagartech.com
dagartech.com





DAGARTECH®
CUSTOM ENERGY SOLUTIONS

info@dagartech.com

T +34 976 141 655

**CUSTOM
ENERGY
SOLUTIONS**

dagartech.com