

Emergency Balance Range

⚡ POWER (PRP / ESP):
226 / 247 kVA (181 / 198 kW)

EU2 EMISSIONS LEVEL:
EU Stage II

📡 FREQUENCY
60Hz

⚡ VOLTAGE
208/120V

CE CE CERTIFIED

BGVW 200 ST

BGVSW 200 ST

1. General technical data

1.1. Version, dimensions and weight

Version	Open	Soundproofed
Dimensions	5K1B-VB	EK1B-VB
L (mm)	2975	3850
W (mm)	1400	1453
H (mm)	2075	2053
Weight with liquids and without fuel (kg)	2150	2900

1.2. Main technical data

Engine	VOLVO TAD840GE-B	
Alternator	STAMFORD UCI274H	
Fuel	Diesel	
Type of execution	G3	
Control panel	DSE 7320 MKII	
Fuel tank (l)	666	666
Sound level-Lp(A) (dB(A)@1m) ¹	N/A (Indoor)	80
Sound level-Lp(A) (dB(A)@7m) ¹	N/A (Indoor)	69
Sound power-LW(A) (dB(A))	N/A (Indoor)	97

¹The sound levels may vary depending on the measurement conditions.

Voltage	PRP ² (KVA/KW)	ESP ² (KVA/KW)	PRP Amperage (A)	ESP Amperage (A)
208/120V	226 / 181	247 / 198	627,3	685,6
220/127V	227 / 182	248 / 198	595,7	650,8
380/220V	223 / 178	244 / 195	338,8	370,7
480/277V	227 / 182	249 / 199	273	299,5

²PRP: Continuous power ("Prime Power"). ESP: Emergency Standby Power according to ISO8528-1.

Tolerance of maximum active power (kW) ±5%

Directives and Regulations

ENVIRONMENTAL CONDITIONS STANDARD ISO 8528-1:2018: 25°C, 100kPa and 30% relative humidity:

- **Prime Power (PRP):** Data on electrical power available at variable load without limit of hours per year. An overload of 10% is allowed for 1h out of 12. According to ISO 8528-1:2018.
- **Emergency Standby Power (ESP):** Data on electrical capacity available at variable load in case of emergency according to ISO 8528-1:2018.

The DAGARTECH Generator bears the CE marking which includes the following directives:

- **2006/42/EC.** Machine Safety Directive.
- **EN ISO 8528-13:2016.** Part 13: Safety. Alternating current generators powered by reciprocating internal combustion engines.
- **2014/30/EU.** Electromagnetic Compatibility Directive.
- **2000/14/EC.** Noise Emissions Directive. Sound power levels evaluated in accordance with the procedure laid down in the directive.
- **Directive 2011/65/EU** on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS 2).

* Confirm the height of the equipment. This value may vary depending on whether a lifting pole is included in the standard scope of supply.

2. Engine specifications

208/120V · 60Hz (1800 rpm)			BGVW 200 ST		BGVSW 200 ST	
2.1. General technical data of the engine	Version		Open		Soundproofed	
	Make and model		VOLVO TAD840GE-B			
	Emissions		EU Stage II			
	r.p.m.		1800			
	Maximum ESP power (kWm)		213			
	Power PRP (kWm)		194			
	Fuel		Diesel			
	No. of cylinders		6			
	Cylinder capacity (c.c.)		7700			
	Compression ratio		17,5:1			
	Cooling system		Water-cooled			
	Type of regulation		Electronic			
	Type of engine/injection/suction		Diesel / direct / Turbocharged			
2.2. Fuel	Type of fuel		Diesel			
	Fuel tank capacity		666		666	
2.3. Consumption and autonomy			Open		Soundproofed	
	Consumption (l/h)		Autonomy (h)		Autonomy (h)	
	PRP	ESP	PRP	ESP	PRP	ESP
	50%	24	-	27,7	-	27,7
	75%	35,2	-	18,9	-	18,9
	100%	47,1	51,7	14,1	12,9	14,1
	12,9					
2.4. Cooling system	Version		Open		Soundproofed	
	Fan flow (l/s)		6,1		6,1	
	Radiator back pressure (Pa)		150		150	
	Fan power consumption (kW)		20			
	Total refrigerant capacity (l)		41			
2.5. Lubrication system	Oil capacity (l)		25			
	Oil consumption (N/A0)		0N/A			
2.6. Intake system	Combustion air intake flow (m³/min)		20,1			

<<Tension>> · <<Frecuencia>> (<<rpm>> rpm)		<<Modelo>>	<<Modelo insonorizado>>
2.7. Starter system	Version	Open	Soundproofed
	No. of batteries	2	
	Battery characteristics	12V 44Ah	
	Start-up voltage (V)	24V	
	Common data for both versions		
2.8. Exhaust system	Exhaust gas flow (m³/min)	19 [PRP]	20,1 [ESP]
	Exhaust gas temperature (°C)	398 [PRP]	407 [ESP]
	Version	Open	Soundproofed
	Exhaust outside diameter (mm)	4" (Ø 101,6)	5" (Ø 127)
	Exhaust attenuation level (dB(A))	-10	-25
	Max. exhaust back pressure (kPa)	10	

Radiator level sensor not available for Baudouin 4M06 series engines.

3. Alternator specifications

3.1. General technical data of the alternator

Voltage		208/120V	220/127V	380/220V	480/277V
Model		STAMFORD UCI274H	STAMFORD UCI274H	STAMFORD UCDI274K	STAMFORD UCI274H
No. of poles		4	4	4	4
Insulation class		H	H	H	H
No. of threads		12	12	12	12
Mechanical protection index		IP23	IP23	IP23	IP23
Voltage Regulator (AVR)		AS440	AS440	AS440	AS440
Voltage regulation		±1%	±1%	±1%	±1%
ESP power 27°C (kVA)		256,3	265	271,4	280
Power PRP 40°C (kVA)		237,5	245	253,2	255
No. of phases		3	3	3	3
Power factor (cos φ)		0,8	0,8	0,8	0,8
		Performance η (%)			
Voltage		50%	75%	100%	110%
<<Tension>>		93,9%	93,7%	93,0%	92,7%
220/127V		94,9%	93,8%	93,2%	93,0%
380/220V		N/A	N/A	91,7%	91,3%
480/277V		93,9%	94,0%	93,6%	93,3%

i Standard regulations that the alternator meets:

AS 1359 | IEC 34-11 | BS EN 60034-1 | VDE 0530 | BS 5000 | CAN/CSA-C22.2-100 | NEMA MG1-32

Low wave distortion: THD (100% load) = 2% | THF < 2%

Complies with: EN61000-6-3, EN61000-6-2 regarding radio interference.

208/120V · <<Frecuencia>> (<<rpm>> rpm)

<<Motor>> | <<Alternador>>

4. Bench Specifications

- Unit mounted on **electro-welded high-resistance steel bench**, painted with electrostatic epoxy-polyester powder paint.
- Connection of the assembly to the bench by means of **anti-vibration dampers**.
- **Fuel tank located on the bench itself**. The engine is equipped with a measuring gauge and fuel system.
- **Tested in a salt spray chamber according to ASTM B-117-09, resistance 500h**.

5. Soundproof Canopy Specifications



i The canopy is part of the scope of supply of the soundproof generator sets.
 Open generators do not include a canopy.

- **Electro-welded canopy made of high resistance galvanized steel** painted with electrostatic epoxy-polyester powder paint
- Interior soundproofing by means of **a lining with soundproofing material**.
- **Attenuation silencer -25dB(A)** for the evacuation of gases to the outside with protective cover.
- **Tested in a salt spray chamber according to ASTM B-117-09, resistance 720H. IP44 mechanical protection degree**.

THE CANOPIES OF THE EMERGENCY BALANCE RANGE ARE MADE OF HIGH-RESISTANCE GALVANIZED STEEL AND ARE ELECTRO-WELDED AND PAINTED WITH ELECTROSTATIC EPOXY-POLYESTER POWDER PAINT.



In addition, they are equipped with a coating with noise-insulating material (polyurethane foam with outer veil). We also incorporated a silencer **attenuation device for the evacuation of gases to the outside**, featuring a rain cap.

*Our canopies are tested in a salt spray chamber according to standard **ASTM B-117-09** (resistance 720H. IP44 mechanical **protection grade**).*

6. Control panel

6.1. Main elements of the control panel

- Protection panel, distribution with **automatic control module** which allows you to work in manual, automatic or signal mode.
- Push button** for **emergency stop**.
- Deep Sea Electronics battery charger**, designed to be permanently connected to the battery and maintain 100% of the charge. The charger switches to float mode when charging is complete:

Model	DSE BC2405 24V, 5A
-------	--------------------

Protections:

- 4-pole magnetothermic protection** against overloads and short circuits.
- Protection fuses** for the control set.

6.2. Circuit breaker

Modelo 208/120V	Chint 800A 4P
Modelo 220/127V	Chint 630A 4P
Modelo 380/220V	Chint 400A 4P
Modelo 480/277V	Chint 400A 4P

6.3. Control module



1. 4 configurable indicator LEDs
2. Generator on load
3. Transfer to the generator (manual mode)
4. Start engine (manual mode)
5. Silence alarm
6. Automatic mode
7. Test mode

8. Manual mode
9. Genset stop
10. MAIN NETWORK transfer (manual mode)
11. Network on load
12. Navigation keyboard
13. Main status and instrument display

Model	DSE 7320 MKII
-------	---------------

DSE 7320 MKII DEEP SEA control card with mains grid monitor. The genset will automatically start up when detecting a fault in the electric power network and it will turn off automatically as well, when the electrical supply is re-established. It can also work in manual mode and by signal. It allows you to monitor a wide range of generator parameters and display information alerts, status and alarms.

The module includes communication ports USB, RS232, RS485, and also DSENet® for system expansion. Possibility of Ethernet networking (plug).

The entire module is easily configurable via PC using the DSE specific software configuration.

It has 132x64p illuminated LCD display with 4 lines of text, 5-key navigation through menus, 9 configurable outputs and 8 configurable inputs, programmable clocks and alarms, reading and displaying parameter values, including RMS values.

Different operating modes: AUTOMATIC mode, MANUAL mode, SIGNAL mode and TEST mode.

Other alternative configurations are available upon request to extend the capabilities of the operation modes.

Environmental Tests that the module passes:

| BS EN 61000-6-2 (electromagnetic compatibility) | BS EN 61000-6-4 (electromagnetic compatibility) | BS EN 60950 (electrical safety) | BS EN 61000-6-2 (Temperature) | BS EN 60068-2-6 (Vibration) | BS EN 60068-2-30 (Humidity) | BS EN 60068-2-27 (Shock).

208/120V · 60Hz (1800 rpm)
VOLVO TAD840GE-B | STAMFORD UCI274H

6.3. Control module


Standard ✓

Model
DSE 7320 MKII

Operating modes

STOP mode	✓
MANUAL mode	✓
TEST mode	✓
AUTO mode	✓

Module configuration options

PC	✓
----	---

Generator readings

Generator voltage (F-F)	✓
Generator voltage (F-N)	✓
Generator current (A)	✓
Generator frequency	✓
Generator load F-N (kW / kVA / kVAr)	✓
Total generator load (kW / kVA / kVAr)	✓
Average generator power factor	✓
Accumulated generator load (kW, kVAh, kWh, kVAh)	✓

Network readings

Network voltages (ph-N)	✓
Network voltages (ph-ph)	✓
Grid frequency	✓
Network current (A)	□
Network load ph-N (kW / kVA / kVAr)	□
Total network load (kW / kVA / kVAr)	□

Engine readings

Coolant temperature	✓
Oil pressure	✓
Engine fuel level	✓
Engine battery volts	✓
Engine speed	✓
Engine run time	✓

Caption

- ✓ Included □ Optional
- ✗ Not available ⓘ Consult

Readings available at control module level.

Confirm the availability of these readings for this generator and engine.

Ask us for further readings in generating sets equipped with electronically managed engines and DSE 7320MKII control module.



DO YOU WANT A SUPERIOR PERFORMANCE CONTROL MODULE?

Contact us and tell us what you need.

208/120V · 60Hz (1800 rpm)

VOLVO TAD840GE-B | STAMFORD UCI274H

6.3. Control module


 Standard 

Model

DSE 7320 MKII

Engine protections

High water temperature	
Low oil pressure	
Low water level	
Fuel reserve by sensor	
Second fuel tank control	
Shutdown failure	
Battery voltage failure	
Battery charge alternator failure	
Overspeed	
Underfrequency	
Failure to start	
Emergency stop	
Maintenance notice	
Maintenance Alert	

Alternator protections

High frequency	
Low frequency	
High voltage	
Low voltage	
Short circuit	
Asymmetry between phases	
Incorrect phase sequence	
Reverse power	
Breaker Trip 4 poles	
Overpressure alarm	

Counters

Hour meter	
Kilowatt meter	
Starter counter	

Caption

-  Included
-  Optional
-  Not available
-  Consult

Readings available at control module level.

Confirm the availability of these readings for this generator and engine.

Ask us for further readings in generating sets equipped with electronically managed engines and DSE 7320MKII control module.



DO YOU WANT A SUPERIOR PERFORMANCE CONTROL MODULE?

Contact us and tell us what you need.

6.3. Control module



Standard ✓

Model

DSE 7320 MKII

Communications

RS232	✓
RS485	✓
USB communication port	✓
Modbus IP	□ DSE 855/890/891
Modbus RS 485	✓
PC Software (Mimic)	✓
GSM/GRPS MODEM	□ DSE 890
Remote display < 1km	□ DSE 2520
Remote monitoring	□ DSE 855/890
Input expansion	□ DSE 2130 8 inputs
Output expansion	□ DSE 2157 8 inputs
SNMP protocol	□ DSE 892

Services

Configurable alarm history	250
External start	✓
Start-up inhibition	□
Network Failure Start	✓
Activation of group counter	✓
Activation of grid and group counter	✓
Control of fuel transfer	✓
Motor temperature control	✓
Forced group operation	✓
Free programmable alarms	✓
Group start function in test mode	✓
Free programmable outputs	✓
Multilingual	✓

Special applications

GPS localisation	□ DSE 890
Calendar scheduler	✓
DSE configuration suite via PC	✓
Front panel module configuration with PIN	✓
Alternative work	✓
Programmable PLC	✓
Power save mode	✓
Alternative configurations	✓
Dummy load control / load shedding	✓ 5 Stage dummy load

Caption

- ✓ Included □ Optional
 ✗ Not available ⓘ Consult

Readings available at control module level.

Confirm the availability of these readings for this generator and engine.

Ask us for further readings in generating sets equipped with electronically managed engines and DSE 7320MKII control module.



**DO YOU WANT A SUPERIOR
PERFORMANCE CONTROL MODULE?**

Contact us
and tell us what you need.

208/120V · 60Hz (1800 rpm)

VOLVO TAD840GE-B | STAMFORD UCI274H

7. Detailed supply scope

Engine

ENGINE VOLVO TAD840GE-B, EU STAGE II OF 1800 RPM, WATER-COOLED AND WITH ELECTRONIC.

- Engine Diesel of 6 cylinders in line and 4-stroke, with regulation Electronic by means of a fuel pump, original from the manufacturer.
- Injection system direct and suction Turbocharged. With particle separator filter, original from the manufacturer.
- Industrial exhaust gas silencer of -10 dB(A).  INCLUDED
- Residential exhaust silencer of <<Nivel de atenuacion esc INCLUDED izado (dB(A))>>dB(A).
- Refrigeration through cooling liquid, fully distributed in the closed circuit run by an engine driven pump.
- Crankshaft-driven pump lubrication system. The filter is a full-flow insert cartridge, front housing, original from the engine manufacturer.
- Air intake system for turbo-fed combustion with two-stage filter, original from the manufacturer.
- Electric motor starting system, battery (no maintenance) with disconnecter and load alternator driven by the starter motor 24V.
- Protection from hot and moving parts.

Alternator

ALTERNATOR STAMFORD UCI274H OF 12 WIRES AND 4 POLES, BRUSHLESS AND WITH ELECTRONIC VOLTAGE REGULATION TYPE AVR (AS440)

- Alternator of 4 poles, brushless. Robust mechanical structure with easy access to connections and components. Insulation class H, coil pitch 2/3 and self-excited AVR.
- With protection degree IP23 and insulation class H.
- Protection with premium epoxy resins. High voltage parts are impregnated under vacuum, which always means very good insulation.

Do you have any queries about the supply?
 Contact us.



Caption:



INCLUDED IN OPEN GENERATOR SETS



INCLUDED IN SILENT GENERATOR SETS

208/120V · 60Hz (1800 rpm)

VOLVO TAD840GE-B | STAMFORD UCI274H

Bench

- Bench made of high-strength electro-welded steel.
- Painted with electrostatic epoxy-polyester powder paint.
- Anti-vibration dampers from the engine block to the bedplate.
- Fuel tank included on the bench itself. Equipped with cleaning record to facilitate maintenance work from 90 kVA of power onward.
- With measuring gauge and installation of fuel to the engine.
- Liquid drainage connection to the outside.
- **Bench tested in a salt spray chamber according to ASTM B-117-09 (500h resistance).**

Soundproofed canopy (not included in open models)

- Electro-welded canopy of high resistance galvanized steel.
- Painted with electrostatic epoxy-polyester powder paint.
- Interior soundproofing by means of coating with noise-insulating material (polyurethane foam with outer veil).
- With IP44 mechanical protection level.
- **Canopy tested in salt spray chamber according to ASTM B-117-09 (resistance 720h).**

Control panel

- **DeepSea Electronics automatic control module, DSE 7320 MKII which allows you to work in manual, automatic or signal mode.**
 - It offers multiple event logging and is fully configurable through DeepSea Electronics' free-access specific configuration software.
 - Three-phase network and group detection with measurement for configurations upon network failure.
- **DeepSea Electronics battery charger DSE BC2405 24V, 5A.**
 - Designed to be permanently connected to the battery and maintain 100% of the charge. The charger switches to float mode when charging is complete.
- **Protections:**
 - 4-pole magnetothermic protection against overloads and short circuits.
 - Protection fuses for the control set.

208/120V · 60Hz (1800 rpm)

VOLVO TAD840GE-B | STAMFORD UCI274H

7. Detailed supply scope

Other equipment

- Interior fuel filling nozzle.
- Tropicalised Radiator for work at 50 °C*
- Prepared for maintenance intervals every 500 hours*.
- Push button for emergency stop.
- Reinforced pole centrally-mounted from 90 kVA (Optional for models below 90kVA).

8. Featured options available



Kit 1: Network failure

Adding an **engine heater** to your generator will ensure that your genset starts smoothly in the event of any failure in the electrical network, and without cold or moisture becoming an issue.




The readings and alarm kit is included within the standard supply scope of the equipment starting from 275kVA of power.

Kit 2: Readings and alarm¹

Your generator can provide you with very useful information in the event of any malfunction, maintenance work, or simply during its operation. If this is an important aspect for you, do not hesitate to include this kit in its equipment, which includes:

- Radiator level alarm sensor.
- Oil pressure reading sensor.
- Temperature reading sensor.

¹ Radiator level sensor not available for Baudouin 4M06 series engines.




Kit 3: Exhaust installation

If you need a **versatile solution for venting gases from your installation to the outside**, choose this kit, equipped with 2 clamps and 3 meters of galvanized steel flexible hose.



✓ AVAILABLE IN OPEN GENERATOR SETS



Check the availability of these options according to the model and, if you don't find what you're looking for, contact us. We have many more options to offer you.

* Consult the specification according to the model.

¹ Maintenance intervals may vary depending on the climate and working conditions.

208/120V · 60Hz (1800 rpm)

VOLVO TAD840GE-B | STAMFORD UCI274H

9. Even more options



24 hour tank


 External ROTH tanks
DUO SYSTEM

AUTONOMY OPTIONS

Increase the autonomy of your generator up to 48 hours, including special tanks

You can choose between different integrated tanks to increase the autonomy of the unit up to 48 hours of operation. You can also incorporate automatic fuel transfer systems for supply from external tanks.

— External tanks:

- External tank 400 l (ROTH DUO SYSTEM).
- External tank 620 l (ROTH DUO SYSTEM).
- External tank 1,000 l (ROTH DUO SYSTEM).
- External tank 1,500 l (ROTH DUO SYSTEM).


 Fuel particle separator
filter

ENGINE - ALTERNATOR OPTIONS

You can choose between different integrated tanks to increase the autonomy of the unit up to 48 hours of operation. You can also incorporate automatic fuel transfer systems for supply from external tanks.

- Electronic engine regulation/management (for models with mechanical regulation).
- Fuel particle separator filter.
- Manual oil drainage pump.
- 6-way fuel valve kit.
- Alternator anti-condensation heaters.
- Superior alternator impregnation systems.
- AVR MX341 + PMG $\pm 1\%$ STAMFORD.
- AVR MX321 + PMG $\pm 0.5\%$ STAMFORD.
- Alternator change supplement (for units with MECC ALTE alternator).

208/120V · 60Hz (1800 rpm)

VOLVO TAD840GE-B | STAMFORD UCI274H



Central lifting pole

MECHANICAL OPTIONS

- Retention tray (see change of dimensions).
- Liquid leak sensor (requires retention tray).
- SilentBlocks for levelling.
- Damping - anti-vibration springs.
- Lifting pole (for generators < 85kVA).
- Non-standard RAL color  AVAILABLE



DSE 2157



DSE 334 network surveillance

COMMUNICATION OPTIONS

- DSE 7320 MKII control card extra price (for models with the DSE 6020 MKII control card in the standard scope of supply).
- DSE 2157 8 potential free output (requires DSE 7320MKII).
- DSE 2130 8 inputs (requires DSE 7320MKII).
- DSE 2548 8 LED diodes (requires DSE 7320MKII).
- DSE 855.
- DSE 890 webnet.
- DSE 7420 module.
- DSE 334 network surveillance.



Socomec motorised switchboard

POWER OPTIONS

- Differential protection.
- As an option, you can include a switch cabinet attached to the generating set.
- Switching with Schneider contactors. 25 to 125 A.
- Socomec motorised switches: $\geq 125A$.

Caption:



✓ AVAILABLE IN OPEN GENERATOR SETS



✓ AVAILABLE IN SILENT GENERATOR SETS





T +34 976 141 655
info@dagartech.com
dagartech.com



¿Necesitas el plano de instalación de la **versión 24 horas**?

Do you need the technical drawing for the **24-hour version**?

Avez-vous besoin du plan d'installation pour la **version 24 heures** ?

Necessita de plano de instalação em versão com depósito de **48 horas**?

Brauchen Sie die Installationszeichnung für die **24-Stunden-Version**?

T +34 976 141 655
info@dagartech.com



¿Necesitas el plano de instalación de la **versión 24 horas**?

Do you need the technical drawing for the **24-hour version**?

Avez-vous besoin du plan d'installation pour la **version 24 heures** ?

Necessita de plano de instalação em versão com depósito de **48 horas**?

Brauchen Sie die Installationszeichnung für die **24-Stunden-Version**?

T +34 976 141 655
info@dagartech.com



info@dagartech.com

T +34 976 141 655

**CUSTOM
ENERGY
SOLUTIONS**

dagartech.com